



Electronic/Glass Fuses

Fast Acting—5mm x 20 mm

Description

- Glass Body
- Fast Acting
- 5mm x 20mm
- 1-1/2" Axial Leads Optional
- 1/10A through 3A, 250VAC - UL Listed and CSA Certified
- 4A through 8A, 125VAC - UL Listed and CSA Certified
- 10A and 15A, 250VAC - UL Recognized

FUS-XX-20

FUSIBLE XX AMPER 20 MM

Standard Fuse Ampere Ratings

CATALOG NUMBER	AXIAL LEAD CAT. NO	AMPERE RATING	VOLTS	I.R. (see notes) *
GGM1/10	GGM-V1/10	1/10A	250V	1
GGM1/8	GGM-V1/8	1/8A	250V	1
GGM2/10	GGM-V2/10	2/10A	250V	1
GGM1/4	GGM-V1/4	1/4A	250V	1
GGM3/10	GGM-V3/10	3/10A	250V	1
GGM4/10	GGM-V4/10	4/10A	250V	1
GGM1/2	GGM-V1/2	1/2A	250V	1
GGM6/10	GGM-V6/10	6/10A	250V	1
GGM7/10	GGM-V7/10	7/10A	250V	1
GGM3/4	GGM-V3/4	3/4A	250V	3
GGM8/10	GGM-V8/10	8/10A	250V	1
GGM1	GGM-V1	1A	250V	1
GGM1-1/4	GGM-V1-1/4	1-1/4A	250V	2
GGM1-1/2	GGM-V1-1/2	1-1/2A	250V	3
GGM1-6/10	GGM-V1-6/10	1-6/10A	250V	2
GGM2	GGM-V2	2A	250V	2
GGM2-1/2	GGM-V2-1/2	2-1/2A	250V	2
GGM3	GGM-V3	3A	250V	2
GGM4	GGM-V4	4A	125V	4
GGM5	GGM-V5	5A	125V	4
GGM6	GGM-V6	6A	125V	4
GGM7	GGM-V7	7A	125V	4
GGM8	GGM-V8	8A	125V	4

*

1: 250VAC @ 35A I.R./125VAC @ 10kA

I.R.

2: 250VAC @ 100A I.R./125VAC @ 10kA

I.R.

3: 250VAC @ 200A I.R./125VAC @ 10kA

I.R.

4: 125VAC @ 10kA I.R.

5: 250VAC @ 100A I.R.